

JJ3014GH-01M-2x4/ATC

Overlock machine with touch panel

2 needle, 4 thread high speed overlock machine with touch panel for easy setting.

Using three sensors, the machine can minimize the thread loss and air loss (the suction for threads only works after the cut).







Feature

3 mode selection

Auto: When the sensor detects the fabric, the presser foot lowers and sewing starts automatically, and finally the chain is cut.

Semi-Auto: Start sewing automatically. A sensor detect the end of the fabric and automatically cuts the chain.

Manual: All sewing is done manually. At the end, the chain is cut by pressing a switch.



JJ3014GH-01M-2x4/ATC

7000 rpm

1~3.8 inch

2mm x 4mm

Plain Seaming

Light to Medium

5.5 mm

Organ DCx27 #9

[User friendly functions]





Touch panel

sensor

Touch panel can adjust the length of the tape and the chain by the number of needles, and change the settings such as the mode.

Sensors detect fabrics and chains, eliminating the need for cutting.

Morimoto Mfg. Co., Ltd. 1-4-17, Suna, Shijohnawate-City, Osaka 575-0001, Japan Printed in Sep. 2024

Tel: (81)72-877-1221	Fax: (81)72-878-9649
www.kansai-special.com	
Fmail: hgeigyo@kansai-special.com	

Specifications

Max. Speed

Needle Type -----Stitch Length

Presser Foot Lift

Diff. Feed Ratio

Gauge Size

Application

Materia

Needle Bar Stroke









Front and back movement (ratio 0.7~2)

