

NFS6604G2FMH-H-S-DD

PROTOTYPE

Machine for flat seaming

4 needle, feed-off-the-arm, top and bottom flat seamer machine with double-cut presser foot.

We have reviewed the oil circulation method, and have created a highly durable specification that circulates oil efficiently and is operator-friendly with less vibration and noise.



NEW S model



Cylinder circumference **140 mm** *Standard 148mm

Features

Super-differential feed mechanism

The conventional differential ratio has been improved to support a differential ratio of 1:0.5~1:1.5.

It is also possible to sew materials with high stretch smoothly.

The differential ratio can be easily adjusted by a manual lever.

Differential adjustment lever



TIP!



★ The stitch length can also be adjusted with a manual lever.

【User friendly functions】



■ Mount base



■ Cushion pad

The mount base has been redesigned and the height can be adjusted to suit the operator.

Cushion pad are available to reduce the burden of work.

Specifications	NFS6604G2FMH
Max. Speed	3500~3800 rpm
Needle Type	Organ FLx118GCS 11
Stitch Length	10~16 inch
Presser Foot Lift	6 mm
Needle Bar Stroke	30 mm
Diff. Feed Ratio	Front-to-back movement (ratio 0.5~1.5)
Gauge Size	5.2mm , 6.0mm
Application	Top & bottom covering
Material	Light to Medium

