PROTOTYPE



WFB5509PA-4WAC

Automatic

waist banding machine

4 needle, cylinder bed, double chain stitch machine with needle feed mechanism for waist banding.

The needle feed amounts can be adjusted with the lower feed dog at the same time by push button.

★Maintainability has been improved by reviewing the puller mechanism.

Features



Double puller It makes possible to

It makes possible to cut materials properly by holding fabric with the front and rear puller.



Original gauge

This model has our original gauge.
Total 44.5 mm as max.

1/8-1/8-1/8-1/8-7/8-1/8-1/8



KANSA

Small distance

By changing the width of the 1/8 needle as desired, It can be used for attaching waist bands to women's and children's clothing.



■ Touch screen

In addition to turning the automatic mode on and off, you can easily adjust belt cutting distance and other things.



Auto skip stitch

The sensor detects the edge of fabric, then the machine automatically skip stitch and cut the fabric.

Specifications	WFB5509PA-4WAC
Max. Speed	3000 rpm
Need l e Type	Organ DVx57 #21
Stitch Length	4~12 stitch/inch
Presser Foot Lift	9 mm
Need l e Bar Stroke	32 mm
Diff. Feed Ratio	-
Gauge Size	1/8-1/8-1/8-1/8-7/8-1/8-1/8 inch
Application	Waist banding
Material	Heavy







